

Separador de Óleo com Reservatório Conjugado em Alta Pressão

R22

**Capacidade Frigorífica - (Kw)
Temperatura de Condensação +45 °C**

Modelos

Entrada e Saída

Temperatura de Evaporação °C

10

0

-10

-20

-30

-40

SVO28-80 / SVOT28-80

1 1/8"

51,25

48,60

45,89

43,13

40,31

37,46

SVO35-80 / SVOT35-80

1 3/8"

71,64

67,95

64,16

60,30

56,36

52,38

SVO42-90 / SVOT42-90

1 5/8"

183,42

97,85

92,40

86,83

81,16

75,43

SVO54-150 / SVOT54-150

2 1/8"

183,42

173,96

164,27

154,37

144,29

134,09

SVO67-200 / SVOT67-200

2 5/8"

236,02

223,85

211,38

198,63

185,67

172,55

SVO67-300

2 5/8"

320,31

303,80

286,87

269,58

251,98

234,18

SVO80-400

3 1/8"

444,25

421,36

397,87

373,89

349,48

324,79

SVO80-550

3 1/8"

572,92

543,39

513,11

482,18

450,70

418,86

Para selecionar gases diferentes da tabela acima (ex.: CO2), consultar a nossa engenharia.



+55 (11) 3611 2770 | +55 (11) 3611 4787



colden@colden.com.br | www.colden.com.br



Rua Antônio Foster, 309 - Vila Socorro
São Paulo - SP - Brasil - Cep 04760-040